

SPECTRA NEWPORT 700c WATERMAKER

PRODUCT SPECIFICATIONS

Production / Day 700 gal (2650 l) Production / Hour 29 gal (110 l)

Power Requirement

24v DC 24A | 48v DC 12A 110v AC 9A | 220v AC 4.5A 18 Watts/1 gal | 4 Watts/1 liter

DC Systems 176 lbs (80 kg) AC Systems 166 lbs (76 kg) Weight

2.5"x10" pleated polyester 5 micron 2.5"x10" pleated polyester 20 micron Pre Filters

Controls Spectra Connect Controller

Compatibility MFD Compatibility

Dedicated thruhull, dry and well ventilated area not to exceed 110F/37C Installation Requirements

Membranes (2) 40" x 2.5" High rejection spiral wound

polyamide

Pump and Motor Carbon vane pump with variable speed

commercial motor

Salt Rejection 99.2%

Temperature Range Max 110F/37C Min 36F/2C

33,000 PPM feed water at 77F/25C **Baseline Conditions**


pH Range 3-11 (typical seawater pH is 8)

Chlorine Tolerance O PPM

Warranty Spectra standard warranty

Shipping Weight 190 lbs (86 kg)

Shipping Dimensions





FACTS

The Newport 700c and 1000c are highly energy-efficient, automated watermakers available in both DC and AC voltages. Motor speed control technology ensures quiet operation whether on an inverter, generator, or directly from the battery bank. The multi-speed capacity optimizes performance in all conditions, automatically switching to low mode to extend prefilter life in challenging feed water. Equipped with the advanced Spectra Connect controller, these systems offer remote operation and monitoring, featuring Fill Tank mode, customizable Auto Run mode, One-Touch Sensor Calibration, and maintenance reminders. Now compatible with Garmin, Raymarine, and Navico/Simrad Multi-Function Display (MFD), the watermaker provides even greater control from the helm, for faster, more convenient operations.

FEATURES

- Control your Spectra Watermaker directly from your Multifunction Display (MFD)
 - Available for most Garmin, Raymarine and Navico/Simrad helm stations
- Completely automated with the Spectra Connect
- Compact modular design
- Spectra's unique Clark Pump ensures efficiency and reliability
- High and low speed operation for customizable power management and
- Low power consumption—can be run on batteries, solar, or wind power

- Whisper quiet
- Commercial grade Magdrive pump with run dry
- Commercial grade, continuous duty motor
- Manual bypass for diversion valve System includes installation kit and tank full
- Z±ION Compatible
- Also available with additional local display



SPECTRA NEWPORT 700c WATERMAKER



14" / 35.5 cm 10" / 25.4 cm 20 cm 33 cm Depth 4" / 10 cm 6.75" / 17 cm Charcoal Filter Depth 6" / 15.2 cm

3.75"

Spectra Connect Display Depth 1" / 2.5 cm



44" / 112 cm High Pressure Clark Pump and Membrane Depth 12" / 30.5 cm

2 Membranes 12.5" 31.75 cm

Newport 1000 3 Membranes

38.1 cm

Newport 700

Optional Components







Katadyn reserves the right to modify products

Katadyn Desalination LLC.

Spectra Watermakers 2220 S McDowell Blvd Ext Petaluma, CA 94954

TEL: 1-415-526-2780 FAX: 1-414-526-2787

E-MAIL: sales@spectrawatermakers.com

www.spectrawatermakers.com