

KATADYN SURVIVOR 06-LS RES - The world's smallest desalinator newly designed for circularity

PRODUCT CHARACTERISTICS

Technology:	Reverse osmosis with patented high-pressure
	energy recovery pump
Salt Rejection:	98.4% in average (97% minimum at 34'000 ppm)
	Desalination degree depends on factors such as
	water temperature and salinity.
Flow:	0.9 l/h ≙ 21.6 l/day*
	0.24 gal/h ≙ 5.7 gal/day*
Pump Rate:	40 Strokes/min
Temperature:	Operation: 2°C to 45°C / 36°F to 113°F
	Storage: -10°C to 45°C / 14°F to 113°F**
Weight:	1.05 kg / 2.3 lbs
Dimensions:	23 x 14.5 x 5 cm / 9.1 x 5.7 x 2 in
Feed Water:	Fresh, brackish or saltwater
Storage:	5 years lifetime / exchange interval***
Material:	Stainless steel, composites and plastics in
	compliance with international food contact
	regulation.
Content:	1 unit compactly packed in sealed bag
Article No. LS:	8021278 for end consumers / single packaging
	GTIN-13: 7612013212788
Article No. LS-1:	8021118 for commercial use / bulk packaging
	(8 pieces per box)
	GTIN-13: 7612013211187



FACTS

- Hand-operated reverse osmosis watermaker for 1 6 people
- Optimum pump frequency: 40 pumps per minute
- Approved by the U.S. Coast Guard
- Prescribed equipment for the "Around-Alone" sailing regatta
- Newly designed for circularity and boosted sustainability***

PRODUCT CHARACTERISTICS > BENEFITS

- The world's smallest desalinator > compact and lightweight
- Provides 0.9 I/h drinking water > ensures survival in emergency situations
- Hand-powered efficiency > off-grid autonomy with effortless pumping
- Military grade impact resistant materials > able in heavy duty missions
- Durable design > extremely reliable for 500h of use*

SHORT PROFILE

The world 's smallest desalinator is approved to replace up to two-thirds of the water ration on board of life rafts. It offers an easy-to-use and reliable way to purify salty, brackish, and fresh water. Ideal for emergency preparedness.



KATADYN SURVIVOR 06-LS RES - The world's smallest desalinator newly designed for circularity

REVERSE OSMOSIS

To desalinate seawater using reverse osmosis, the dissolved salts are filtered through a semipermeable membrane. Only 10% of the water is allowed to pass through the membrane, while the remaining 90% flows past it. This serves a dual purpose of continuously cleaning the membrane (self-cleaning effect) and carrying away the rejected salts. The semipermeable membrane's small pores ensure the production of extremely pure drinking water under high pressures (normally 55 bar) by blocking impurities, salts, and other contaminants. Reverse osmosis is a widely used technology worldwide, finding applications in various industries such as the semiconductor industry and medicine.

KATADYN'S PATENTED ENERGY RECOVERY SYSTEM

The Katadyn Energy Recovery system takes advantage of stored energy in the high-pressure reject water that is typically wasted in conventional reverse osmosis systems. The pressurized reject water is recirculated to the back side of the piston to aid the next stroke. This leads to higher energy efficiency and a more sustainable water purification process, as less external energy is needed to achieve freshwater.



APPROVALS

- Approved desalinator as defined in the 1983 conditions of the Safety of Life at Sea Convention (SOLAS)
- United States Coast Guard (USCG) certificate no. 160.058/7/0
- Federal Aviation Administration (FAA): fulfills Federal Aviation Requirement (FAR) Section 135, 121

DISCLAIMER

- * The maximum flow rate based on tests carried out on new membranes at 20°C / 68°F. The minimum measured output after 500-hour usage corresponds to 0.75 l/h (0.2 gal/h), while SOLAS require 0.5 l/h (0.13 gal/h) at 500-hour stage.
- ** Storage conditions comply with IMO MSC 81(70) for 8h temperature cycles of -30°C to 65°C / -22°F to 149°F packed in a life raft. Unit is not intended for long term storage at these temperature peaks.
- *** Product cycle has been modified such that the Survivor O6-RES is returned to Katadyn after a usage/storage period of 5 years and will be recycled.

Katadyn reserves the right to modify products

Version: 15.04.2024

Katadyn Products Inc. | Pfäffikerstrasse 37 | 8310 Kemptthal | Switzerland Tel: +41 44 839 21 11 Fax: +41 44 839 21 99 info@katadyn.ch | www.katadyn.com